



MRP料號(B)	客戶料號(F)	成品長度(L)
	HDUL-03	3000+/-70mm
	HDUL-05	5000+/-100mm

(A).Wire Pin Assignment and Wire Description.

CN.1	Signal Assignment	CN.2	WIRE
1	TMDS Data2+	1	WHITE
2	TMDS Data2 Shield	2	DRAIN
3	TMDS Data2-	3	GREEN
4	TMDS Data1+	4	WHITE
5	TMDS Data1 Shield	5	DRAIN
6	TMDS Data1-	6	ORANGE
7	TMDS Data0+	7	WHITE
8	TMDS Data0 Shield	8	DRAIN
9	TMDS Data0-	9	BROWN
10	TMDS Clock+	10	WHITE
11	TMDS Clock Shield	11	DRAIN
12	TMDS Clock-	12	BLUE
14	Utility/HEAC+	14	WHITE
17	DDC/CEC Ground	17	DRAIN
19	Hot Plug Detect	19	YELLOW
13	CEC	13	PURPLE
15	SCL	15	BLUE
16	SDA	16	GREEN
18	+5V Power	18	RED
SHELL		SHELL	BRAID

(B). Electrical Testing :

- a. OPEN/SHORT:100% Testing Line-Process.
- b. HI-POT: 200V AC/0.01sec.
- c. INSULATION RESISTANCE:10MΩ(MIN) 200V DC
- d. CONDUCTION RESISTANCE:7Ω(MAX)

/	KG	PVC Molded:50P Color:黑色	3
2	SET	HDMI CONNECTOR HOUSING BLACK TER: GOLD PLATED(鍍金) SHELL GOLD PLATED(鍍金)	2
/	mm	HDMI CABLE[(34AWG*2C+EAM)*5+34AWG*4]+AB Cu- BRAID:85% OD:4.5mm Jacket PVC 黑色	1
Q'TY	U/M	MATERIALS LIST & SPEC. DESCRIPTION	ITEM
		DWN By.	<b>Arvanics Corporation</b>
		CHK By.	
		APVD By.	
		NAME :	HDUL-03, HDUL-05
		SIZE SHEET:	DRAWING NO.
		REV:	
Product MRP Code :		Customer No.:	Customer Part No.:

DIMENSIONS:	TOLERANCES UNLESS OTHERWISE SPECIFIED:
	0 PLC ±
	1 PLC ±
	2 PLC ±
	3 PLC ±

變更履歷	△				
	No.	Revision	Revision Content	Revision Date	Revision BY
	4			3	